

# CAPP

D E N M A R K

## CappAero384

MULTICHANNEL PIPETTES

a e r o 3 8 4 . c a p p . d k

### CAPPAERO™ MULTICHANNEL PIPETTES FOR 384-WELL PLATES

MOST APPLICATIONS INVOLVING 384-WELL PLATES ARE PERFORMED USING AUTOMATED SYSTEMS. CAPP PROVIDES THE WORLD'S ONLY ALTERNATIVE FOR THE QUICK AND HIGH PRECISION PIPETTING OF 16-, 48-, OR 64-WELLS AT ONCE WITHOUT THE USE OF EXPENSIVE, AUTOMATED EQUIPMENT.

### IDEAL FOR 384 WELL LIQUID HANDLING

THE CAPPAERO™ 48 & 64 CHANNEL PIPETTE ALLOWS FOR PIPETTING LARGE SAMPLES WITHIN A SHORT PERIOD OF TIME WHILE REDUCING THE WORKLOAD. THE CAPPAERO™ IS GENERALLY APPLICABLE FOR ALL TRANSFERS OF LIQUIDS FROM RESERVOIR AND 384 DEEP-WELL PLATES INTO 384 WELL TEST PLATES, AND IT OFFERS VERY OBVIOUS ADVANTAGES IN PCR, MICRO ARRAY, AND MALDI SPECTROMETRY TECHNIQUES. CAPP 384 MULTICHANNEL PIPETTES FEATURE LIGHTWEIGHT CONSTRUCTION AND PRODUCE THE MOST CONSISTENT AND RELIABLE LIQUID TRANSFER RESULTS IN ONE ERGONOMIC SOLUTION.



EXPELLPLUS™ LOW RETENTION AND EXPELL™ TIPS

### HIGH QUALITY, LOW RETENTION TIPS

CAPP OFFERS A RANGE OF EXPELLPLUS™ TIPS WHICH ARE SPECIFICALLY DESIGNED TO PERFECTLY FIT THE CAPP RANGE OF 384 WELL PIPETTING. DUE TO SPECIAL POLYMERS AND AN EXTREMELY SMOOTH INSIDE SURFACE, THE EXPELLPLUS™ TIPS FROM CAPP® VIRTUALLY ELIMINATE SAMPLE RETENTION, AND REDUCE THE BINDING OF DNA, RNA, AND PROTEINS TO A MINIMUM. THE RANGE ALSO INCLUDES A FILTER TIP VERSION TO EFFECTIVELY PREVENT CROSS CONTAMINATION DUE TO AEROSOL FORMATION (SUCH AS DNA), AND DANGERS FROM TOXIC, INFECTIOUS, RADIOACTIVE OR OTHER HAZARDOUS MATERIAL'S CARRY OVER.

 CAPP APS  
 LANDBRUGSVEJ 10  
 DK-5260 ODENSE  
 DENMARK

TEL. (+45) 6613 6140  
 FAX. (+45) 6613 2770

MAIL: INFO@CAPP.DK  
 WEB: WWW.CAPP.DK



## Ordering Info

### Standard Line

CAT. No.	DESCRIPTION	INACCURACY %	IMPRECISION %	COLOR
C02-16	CAPP MULTI PIPETTES, 16-CHANNEL, 0.2-2 UL	4.00	2.00	
C10-16	CAPP MULTI PIPETTES, 16-CHANNEL, 0.5-10 UL	2.00	1.00	
C50-16	CAPP MULTI PIPETTES, 16-CHANNEL, 5-50 UL	1.40	0.60	
C10-48	CAPP MULTI, 48-CHANNEL, 0.5-10 UL	4.00	2.00	
C10-64	CAPP MULTI PIPETTES, 64-CHANNEL, 0.5-10 UL	4.00	2.00	

### Soft Line

CAT. No.	DESCRIPTION	INACCURACY %	IMPRECISION %	COLOR
C02-16-SL	CAPP MULTI PIPETTES, 16-CHANNEL, 0.2-2 UL	4.00	2.00	
C10-16-SL	CAPP MULTI PIPETTES, 16-CHANNEL, 0.5-10 UL	2.00	1.00	
C50-16-SL	CAPP MULTI PIPETTES, 16-CHANNEL, 5-50 UL	1.40	0.60	

### ExpellPlus™ low retention tips

CAT. No.	DESCRIPTION	QTY/PACK	PACKS/CASE
5030003C	EXPPELLPLUS 0.2-10UL, RACKED, STERILE	10 x 384	5
5030004C	EXPPELLPLUS 0.2-10UL, RACKED, STERILE, FILTERED	10x384	5
5030005C	EXPPELLPLUS 0.2-50UL, LONG, RACKED, STERILE	10 x 384	5
5030006C	EXPPELLPLUS 0.2-50UL, LONG, RACKED, STERILE, FILTERED	10 x 384	5

### Starter Kits

CAT. No.	DESCRIPTION
SK-16-XX	ONE 16-CHANNEL PIPETTE FREE OF CHOICE, STAND, 3 RACKS OF TIPS AND TIMER
SK-64-XX	ONE 64-CHANNEL PIPETTE FREE OF CHOICE, STAND, 3 RACKS OF TIPS AND TIMER

Distributed by ARC Sciences Ltd., PO Box275, Alton, Hampshire, GU4 9FJ – t:01420 549922

[enquiries@arcsciences.com](mailto:enquiries@arcsciences.com)

[www.arcsciences.com](http://www.arcsciences.com)